

# Application Instructions

## Woodoc 45 Water-Borne Tile and Cement Sealer

### WHERE TO USE PRODUCT

For interior/exterior use. Clear, gloss or matt water-borne sealer. For unglazed, porous tiles, cement, stone & brick. The product is water-repellent and stain & oil resistant.

### HOW TO PREPARE THE SURFACE

Surface must be completely clean from dust, oil, wax, grout or other sealers. If washed, let surface dry completely (at least 8 hours). Consult with tile manufacturer for special cleaning and preparation instructions before product is used. Test on small area to ensure porosity - the product must penetrate surface immediately after application. Do not use on old surfaces if not completely clean and oil-free.

### HOW TO APPLY THE PRODUCT

Mix well before use. Do not dilute. Use large paint brush or sheepskin applicator. Apply one liberal coat; do not allow pooling. Very porous substrates may require 2 or 3 coats. Each coat must dry completely.

Note: Allow 24 hours before using sealed surface.

**COVERAGE:** 5 - 12 m<sup>2</sup> per litre depending on porosity of substrate/surface.

### WARRANTY.

Rekara Mills (Pty) Ltd warrants that this product, as consigned from our factory, was subject to strict quality assurance tests and meets durability, safety, and quality standards. The product must be used, stored and handled strictly according to the instructions and warnings provided on the container and/or any pamphlet attached thereto or made available with the product. All such instructions and warnings must be strictly adhered to otherwise Rekara Mills (Pty) Ltd accepts no responsibility for the use or performance of this product.