
Woodoc 25 Water-Borne Specification Sheet



Typical Application:

Suitable for application to all interior wooden floors and -stairs. Only for interior use. Resistant to normal domestic wear and tear.

Woodoc 25 Water-Borne FLOOR is not an industrial product.

Product Features:

Woodoc 25W creates a clear or white glossy, matt or ultra-matt finish. It is a remarkably tough, wear- resistant floor sealer and lends a characteristic deep polished/natural matt look to floors.

- Does not yellow.
- Low-odour.
- Easy application.
- Water-, alcohol-, heat- and stain-resistant.
- Penetrates wood, binds with it and lends a flexible yet strong and resistant surface finish.
- Suitable for all types of wood.
- Non-toxic once dry.
- Fills the grain of open-grained woods.
- Floor surface can be slippery after sealing with this product.
- Complete how-to-use instructions on label.

NOTE: Wooden floors treated with Woodoc 25W should not be washed with water and detergents/soap. Clean with a damp cloth.

No: W25W/05 Dated: **02/04/19**

Name:

Woodoc 25W - Water-Borne Wood Floor Sealer - Gloss, Matt or Ultra-Matt (Clear or White)

Description:

Gloss, matt or ultra-matt finish

Coverage:

First coat 10-12 m²/litre. Subsequent coats 12-14 m²/litre. 3 coats (average) 3,3 m²/litre.

Application:

Preferably by brush. Clean brush with water before dry.

Dilution:

Do not dilute product.

Drying Time:

Drying will vary, depending on moisture and atmospheric conditions.

Product Properties:

Clear or White, lead-free, interior wood sealer. Formaldehyde-Free.

Wax Content:

None.

Compatibility:

Water.

Non-Compatibility:

Acetone, Lacquer Thinners, Benzene and other solvents.

VOC: This product contains max. 75 g/l VOC **Packaging:** 1 litre and 5 litres (20 litres available on request.

ALWAYS READ THE DIRECTIONS ON THE TIN BEFORE STARTING WORK.



Manufactured and marketed by: Rekara Mills (Pty) Ltd PO Box 16, Fort Beaufort 5720, South Africa Tel +2746 645 1109 Fax +2746 645 1538